

Name \_\_\_\_\_

Utility \_\_\_\_\_

MEUW Safety Training  
Lifting and Rigging Safety Part 2  
Pages 129, 138 – 146

A sling **should / shall** (circle correct answer) not be pulled from under a \_\_\_\_\_ when the load is \_\_\_\_\_ on the sling.

Operators **should / shall** (circle correct answer) not leave their position at the \_\_\_\_\_ of cranes, hoists, derricks, or other lifting devices while the load is suspended except where all of the following conditions are met:

- (1) The operator remains adjacent to the \_\_\_\_\_ and is not engaged in any \_\_\_\_\_.
- (2) The load is to be held \_\_\_\_\_ for a period of time exceeding \_\_\_\_\_ lifting operations.
- (3) The \_\_\_\_\_ person determines that it is safe to do so implements measures necessary to restrain the boom \_\_\_\_\_ and \_\_\_\_\_, load, \_\_\_\_\_, and \_\_\_\_\_ or stabilizer functions.
- (4) Barricades or caution lines, and notices, are erected to prevent \_\_\_\_\_ employees from entering the fall zone. No employees, including those listed in 29 CFR 1926.1425(b)(1) through 29 CFR 1926.1425(b)(3), 29 CFR 1926.1425(d) or 29 CFR 1926.1425(e) are permitted in the fall zone. **These standards will be reviewed in the future during a safety meeting.**

Slings **should / shall** (circle correct answer) be padded or protected from the sharp edges of their loads.

When an aerial lift device is in use, the \_\_\_\_\_ of the vehicle **should / shall** (circle correct answer) be set. \_\_\_\_\_ and outriggers (if equipped) **should / shall** (circle correct answer) be used to provide added protection. The truck **should / shall** (circle correct answer) be approximately level when viewed from the rear.

When U-bolt wire rope clips are used to form eyes in winch lines, the number used and the spacing provided shall be in accordance with Figure 503-2. The U-bolt shall be applied so that the U section is in contact with the \_\_\_\_\_ of the rope.

Shackle pins **should / shall** (circle correct answer) never be replaced with \_\_\_\_\_ or other \_\_\_\_\_ devices.

Aerial devices **should / shall** (circle correct answer) not be “field modified” unless such modification is **approved / certified** (circle correct answer) by the manufacturer. The \_\_\_\_\_ portion **should / shall** (circle correct answer) not be altered in any manner that might reduce its **lifting / insulating** (circle correct answer) value.

Slings used in a \_\_\_\_\_ hitch **should / shall** (circle correct answer) have the load \_\_\_\_\_ to prevent slippage. Load limits of the boom and aerial lift device **should / shall** (circle correct answer) not be exceeded. \_\_\_\_\_ (sudden stops or starts) of the equipment shall be avoided.

Winch lines, ropes, or wire cables **should / shall** (circle correct answer) not be guided by \_\_\_\_\_ when standing within \_\_\_\_\_ of the drum or sheave.

Signals to the equipment operator **should / shall** (circle correct answer) be given by \_\_\_\_\_ person designated to perform this task and **should / must** (circle correct answer) be maintained throughout the operation between the \_\_\_\_\_ and the \_\_\_\_\_ person

No employee **should / shall** (circle correct answer) be under a suspended load or inside the \_\_\_\_\_ of a winch line. No employee shall stand or work near a \_\_\_\_\_, \_\_\_\_\_, or \_\_\_\_\_ under tension unless the nature of their work requires it.

Annual/comprehensive inspections must be \_\_\_\_\_, maintained, and retained for a minimum of \_\_\_\_\_ months, by the **employer / inspection** company (circle correct answer) that conducts the inspection. The information **should / must** (circle correct answer) contain at a minimum: items \_\_\_\_\_ of the inspection, and the name and signature of the person who conducted the inspection and \_\_\_\_\_.

Inspections that took place (each shift), **should / shall** (circle correct answer) be documented and maintained by the employer that conducts the inspection, and must meet the following criteria:

- (1) Contain items \_\_\_\_\_.
- (2) \_\_\_\_\_ and \_\_\_\_\_ of the person who conducted the inspection and the \_\_\_\_\_.